

# FRONTLINE

Quality  
with  
Exceptional  
Value!



## FRO-TS222

Introducing the FRO-TS222 tire machine. This economical, yet rugged design was built to take punishment. Don't let the exceptional value fool you. It is a standard design rim clamp, that has the quality of more expensive machines. This machine is up to the tough task of changing tires. The manufacture has integrated ways to improve longevity of the machine. Such as, a galvanized bead breaking cylinder, and a pedal/valve assembly that can be removed easily for servicing. The FRO-TS222 is ideal for individuals that need an entry level machine but do not want to sacrifice quality or performance.

### OPTIONAL PROTECTION



G800A98 → 20"-22"



G800 A8 (2 x kit)  
G800 A8K (10 x kit)



G800 A11


### \*OPTIONAL HELPER ARM



### PLUS 91N

Bead top pressing  
and tire lifting  
device for large  
and special tires.

IN	OUT
13"-24,5"	11"-22"



- Heavy duty structure to guarantee proper working conditions at all times
- Bead breaker: galvanized cylinder with simple operation
- Rigid self-centering chuck and wide clamping range

The pedal assembly can be removed allowing easy servicing.  
Tool with intergrated protection for alloy rims.

### TECHNICAL DATA

Operating pressure	120 - 145 PSI
Motor	120 Volt / 3/4 hp
Chuck rotation speed	7.3 RPM
Max. torque to chuck	885 ft lbs
Clamping capacity external	11"-22"
Clamping capacity internal	13"-24,5"
Max. tire diameter	1030 mm (40,5")
Max. rim width (inches)	12"
Beak breaker pressure	3000 kg / 6000 lbs